



OHIO


FBM & FHM Metric Levelers




FBM




FHM




Part Number	Thread Size / Pitch	Hex Across Flats	Thread Length	Pad Diameter	Hex To Bearing Surface
		W	L	A	B
FBM 08040	M8 x 1.25-6g	9.5	40.0	25.4	20.6



The FBM leveler is a top quality unit that features a thick, vibration dampening, gray rubber base with a durometer of 70 to 80. The FBM will not mar or streak floors or deface painted or specially finished surfaces. The FBM has a hex shoulder and a turnable screw to ease adjustment under load. This leveler fills a need for a sturdy, high quality unit which provides leveling and improved appearance.



Thread Size / Pitch		M6 x 1-6g	M8 x 1.25-6g	M10 x 1.5-6g	M12 x 1.75-6g
Base Across The Flats	A	14.0	19.0	22.0	25.0
Base Thickness	B	2.6	3.2	3.9	4.6
		2.3	2.9	3.6	4.3
Length (Under Head) L Up To 25mm + 0.0 - 0.8	25.0		FHM 08025		
	30.0	FHM 06030			
Over 25mm To 50mm + 0.0 - 1.6	35.0		FHM 08035	FHM 10035	
	40.0		FHS 08040 *	FHS 10040 *	
Over 50mm + 0.0 - 2.3	60.0			FHM 10060	
	65.0			FHS 10065 *	FHM 12065



L = Overall Leng



The metric FHM leveler is strong, economical and one piece construction. Rolled threads extend full length for maximum adjustment. Exposed base prevents dirt buildup and offers the advantage of easy cleaning. The base is beveled to facilitate moving.

* Easily adjusted with standard wrenches, several sizes are available with a slotted end for screw driver adjustments.



Material:C1010 High-Welding Quality, Low Carbon Steel

Finish:Plain, Unless Specified

Threads:ASME B1.13M-2005



The Ohio Nut and Bolt Company

Sales Office: Buckeye Fasteners • "Your Factory Source"

5250 West 164th Street • Cleveland Ohio 44142

Ph: (800)-437-1689 • Ph: (216)-267-2240 • Fax: (216) 267-3228

www.BuckeyeFasteners.com

A Division of Fastener Industries Inc. — An Employee Owned Company

© Copyright 2012 The Ohio Nut and Bolt Company

